

**PLEASE PASS TO YOUR  
ELECTRICAL  
DESIGN DEPT.**

Dear Customer

Welcome to our March bulletin.

You may possibly remember that back in January 2004 I announced the formation of a new Raytel Group company: Raytel Controlgear Supplies Ltd. I am very pleased to advise that they have managed to establish themselves very successfully in a competitive market.

The General Manager, Mr David Wilson, tells me that "customers have been very impressed with the quality and reliability of the product range, and of course the very competitive prices".

Just to remind you, their product range includes:

- Push Buttons • Indicator Lamps • Contactors
- MCBs • SSR • Switches • Plugs and Sockets
- Terminals • Wiring Accessories • Fuses and Fuse Holders • Relays • Load Disconnectors
- ELCBs • and many other associated products.

For further details contact David Wilson on 01268 740290 or [action@raytelcontrolgear.co.uk](mailto:action@raytelcontrolgear.co.uk).

Yours sincerely  
Gary Brookes  
Managing Director

**PRODUCT FOCUS**

**THE PRODUCT**

This month we highlight the popular Category 3 or 4 link programmable F127 safety relay. Measuring just 22.5 mm wide this relay provides 3 normally open and 1 normally closed contacts and has a choice of 24V ac/dc, 115V ac or 230V ac supply options.

The emergency stop safety relay F127 complies fully with EN60204, EN292 and EN954-1. The relay employs failsafe electronic circuiting for self checking and short circuit/link monitoring functions.



**VERSIONS**

- F127x10** Auto Reset or non-monitored manual reset - Category 3 applications
- F127x11** with monitored manual reset - Category 4 applications
- F127x20** Auto Reset, with removable terminals option - Category 3 applications
- F127x21** Monitored manual reset, with removable terminals Category 4 applications

**APPROVALS**

UL, CSA, BG - Approved.

**SPECIFICATION**

Supply Voltage	24V ac/dc, 115V ac, 230V ac (-20% to +10%)
Control Voltage	24V dc (S11/S21)
Minimum Return Voltage	19.2V (S12/S22)
Contacts	3NO, 1NC (5µm gold plated)
Maximum Switching Capacity	6.8A ac, 6A dc
Other Specifications	See technical data sheet.

**PRICES**

	Aux 115V ac 230V ac	24V ac/dc
<b>F127x10</b> Automatic Reset or - Non-monitored manual reset	£91.59*	£88.24*
<b>F127x11</b> Monitored manual reset	£91.59*	£88.24*
<b>F127x20</b> Removable Terminals - Automatic Reset	£94.38*	£91.03*
<b>F127x21</b> Removable Terminals - Monitored manual reset	£94.38*	£91.03*

\* Discounts available for quantity or regular orders.

**DELIVERY**

All non removable terminal strip versions available from stock. Versions with removable terminal strips - please allow 7 to 10 days.

**USEFUL CONTACTS**

**Instrumentation, Industrial Relays**

Tel: 01268 749301

**Safety Products**

Tel: 01268 749302

**Temperature/Pressure and Rotational Products**

Tel: 01268 749303

**Special Projects**

Tel: 01268 749300

**Customer Service**

Tel: 01268 749300

**Web Site**

[www.rayleigh.co.uk](http://www.rayleigh.co.uk)

**Email**

[sales@rayleigh.co.uk](mailto:sales@rayleigh.co.uk)

**WEB SITE**

For up-to-date company news, please visit our website at

**[www.rayleigh.co.uk](http://www.rayleigh.co.uk)**

We would welcome your comments.

**RAYLEIGH INSTRUMENTS LIMITED**

**FAX BACK**

**01268 749309**

Company Name:

Address:

Postcode:

Tel:

Contact:

Position:



Please send details of your **F127** Safety Relay.