

PRO1250 DIN Rail Series Three Phase

Introduction

The PRO-1250 is the 3 phase version in the PRO Series with a 5 year warranty, just like for all other products in the PRO range.

The meter is built with the highest quality components. There is a 10/100A direct meter and a -/5A version for measuring with current transformers. In the digital meter for current transformers are 2 buttons to set ratio of the used current transformer.

Functions and features

- DIN rail mounting
- LCD 6+1 or Mechanical register
- SO output
- Easy installation
- High price/quality ratio
- Indoor meter
- 5 year warranty
- MODBUS RTU (Remote Terminal Unit) available
- 5A CT version for measuring with current transformers available
- MID approval expected in 2009

Technical specifications

Voltage	230 / 400V AC
Frequency	50 / 60Hz ±10%
Current	100A or -/5A
Power consumption	≤ 2W / 10VA per phase
AC voltage withstand	2KV – 1 minute
Impulse voltage withstand	6KV – 1,2µS waveform
SO output	SO according to DIN43864
Temperature range	-20°C ~ +55°C
Case	126 mm DIN Rail mounted
Dimensions (wxhxd)	126x100x65mm
Accuracy Class	1
Packaging dimensions	55x33x26.5cm - 15.1kg (24pcs/ctn)



PRO1250A



PRO1250D

Outline dimension

